



808 CUT AND POLISH COMPOUND

Technical Data Sheet No 911



General Technical Description

A high performance one step polishing compound that can be used to cut and polish at the same time.

It eliminates deep sanding marks and scratches from P1500 without burning in during high intensity, while it completes the polishing with a permanent hologram-free mirror finish.

Special formula with new technology abrasives that can cut and polish all modern types of topcoats.

Silicon-free.

Surface

All 2K acrylic finishes including clear coats, original manufacturer's, fresh and aged cured paints.

Pretreatment / Cleaning of substrate



Always use a clean soft cloth to wipe the surface, leaving it clear of dust, oils and any other contamination.

Product Application:

1. Shake well before use and ensure the application surface is clean from dust and properly cured. Polishing on hot surfaces and at direct sunlight should be avoided.
2. Use HB BODY white pad or a hard pad initially in case of a recently coated surface, or a wool pad in case of an old coated surface.
3. Apply the compound on the pad and then spread all over the surface.
4. Compound using medium pressure at 900-1200 rpm. Repeat the same stage in case of very deep scratches.
5. It is recommended to use the HB BODY yellow pad and repeat stages 3 and 4 increasing the speed to 1200-1500 rpm to achieve a mirror finish.
6. To remove holograms use the HB BODY waffle pad and repeat stage 3 and 4 increasing the speed to 1200-1500 rpm. In case of permanent holograms especially on dark shades use 807 SEAL POLISH.
7. At the end of procedure or between steps clean surface with a soft cloth without edges.



Always wear protective equipment



Follow the application instructions mentioned in this TDS

Abrassiveness:
10 (min = 1, max = 10)

Gloss:
8 (min = 1, max = 10)

Specific Gravity:
1.26 ± 0.05 g/cm³

Colour:
White

Viscosity:
7 - 9 Pas @ 20°C (68°F)

pH Value:
9.5 @ 20°C (68°F)

Remarks:

- Best results when used with HB BODY pads and supplemented with 807 SEAL POLISH.
- It can be used by countries that do not adopt the VOC legislation as well.

Storage shelf life:

- Store in a cool place +5°C - +25°C (+41°F - +77°F). Guaranteed shelf life of 24 months in unused original containers.

This is a waterborne, silicone and ammonia free, polishing compound. Does not contain silicone. It is used for polishing high gloss surfaces.

For professional use only. The information displayed on this sheet has been carefully selected through a series of laboratory investigations. It is based on our best knowledge at the time of issue. The data is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check for newer updates or further information if needed for his intended purpose. The intellectual property of this product, trademarks and copyrights is protected. All rights reserved. The relevant Material Safety Data Sheet and warnings displayed on the label must be read carefully. We may modify and / or discontinue operation of all or portions of this information at any time in our sole discretion, without any notice and assume no responsibility to update the information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

Issue 1 / 2020, March 2020